



New Design More Easily

Wireless N300 Easy Setup Router N301

The N301 Wireless N300 Easy Setup Router is designed to setup more easily for the home user. It complies with IEEE802.11n, delivers wireless speeds of up to 300Mbps, making it perfect for everyday web activities like email, chat, streaming videos, online gaming and more. The N301 can also work as a client router to connectISP network wirelessly or uplink AP to share the Internet to every corner, eliminating the dead point.







Easy to Setup

With just three easy steps, get your secure wireless network up and running in minutes.

Secure WiFi at a push of WPS button

Compatible with WI-FI Protected Setup[™] (WPS), N301 features WPS that allows users to almost instantly setup their security simply by pressing the "WPS" button automatically establishing a secure connection. Not only is this faster than normal security setups but more convenient in that you don't need to remember a password.



Advanced Wireless Security

N301 offers multi-level wireless encryption options to prevent unauthorized access and protect your important data.

1.64/128bit WEP、WPA-PSK、WPA2-PSK

2. Wireless Access Control based on the mac address of wireless adapter



Wireless WAN

N301 can work as client mode to connect to ISP network or uplink AP wirelessly to share the Internet to every corner, eliminating the dead point.







Parental Control

Support parental control function like IP/MAC filter, you can limit the time to access the internet and block the websites.

How it Works

How to make wireless magic, start with Internet service and a modem then connect a Tenda router. The router broadcasts a wireless signal that lets you easily connect your devices and smart appliances.

Specifications

| Compliant Standard | IEEE 802.3/3U IEEE 802.11n/g/b | |
|------------------------|--|--|
| Wired Interface | 1 10/100Mbps WAN Port | |
| | 3 10/100Mbps LAN Ports | |
| Antennas | 2 fixed 5dbi Omni Directional antennas | |
| Button | 1 Reset/WPS Button | |
| Item dimensions(L*W*H) | 127.4mm*90.5mm*26mm | |
| Wireless Features | - F | |
| Frequency Range (GHz) | 2.412GHz-2.472GHz | |
| | IEEE 802.11n: up to 300Mbps | |
| Wireless Link Rate | IEEE 802.11g: up to 54Mbps | |
| Wireless Security | IEEE 802.11b: up to 11Mbps | |
| | 64/128bit WEP | |
| | WPA-PSK | |
| | WPA2-PSK | |
| | WPS support | |
| | AP | |
| Working Mode | WISP | |
| | WDS Bridge | |
| Wireless Function | Enable/Disable Wireless Radio | |
| | Wireless Access Control | |
| Reception Sensitivity | b mode:1M -92dBm@8% 11M -87dBm@8% PER; | |
| | g mode:54M -72dBm@8% PER; | |



Г

Telecom Distributor Ecuador



| Software Features | |
|--------------------------|--|
| Internet Connection Type | Dynamic IP、PPPOE、Static IP、L2TP、PPTP |
| DHCP | Built-in DHCP server |
| | DHCP Client List |
| | Address Reservation |
| Virtual Server | Port Forwarding |
| | DMZ Host |
| Parental Control | Client Filter |
| | Mac Filter |
| | Websites Filter |
| | No-IP |
| Dynamic DNS | dyndns |
| VPN Pass-Through | PPTP |
| | L2TP |
| Other Advanced Function | Bandwidth Control |
| | Mac Address Clone |
| | Remote Web Management |
| | System Log |
| Others | |
| Package Contents | Wireless N300 Easy Setup Router N301 |
| | Quick Installation Guide |
| | Ethernet cable |
| | Power adapter |
| | Resources CD |
| Environment | Operating Temperature: 0°C~40°C |
| | Storage Temperature: -40°C~70°C |
| | Operating Humidity: 10%~90% non-condensing |
| | Storage Humidity: 5%~90% non-condensing |
| Certificates | FCC, CE, RoHs |

Caran N4-117 y Pasaje "D" Aguirre Terán (Calderón) Quito – Ecuador www.jastech.com.ec

 C 2013 SHENZHEN TENDA TECHNOLOGY CO., LTD, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co., Ltd in China and/or other countries. Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.