

NETWORK CAT 6

Copper Solutions

CAT 6

Reliable 6 cable is the answer given by LanPro to the large demand imposed by today's high performance applications, at reasonable prices.

Reliable 6 is UL, ULc, and ETL approved and exceeds TIA/EIA 568-B.2-1 specifications for Category 6 (CAT 6).

Now with "flexible-x" construction, reliable 6 cable isolates the pairs throughout the length of the cable, improving field installation as well as performance.

Reliable 6 cable available for immediate delivery on gray and blue colors, other colors available under request.

Exceeds TIA/EIA 568-B.2-1 Category 6 SPECS.


For Gigabit Ethernet, 100BASE-Tx, token-ring, 155 Mbps ATM, 100 Mbps TP-PMD, ISDN, analog (Broadband, Baseband), digital video and Voice over IP (VoIP), it can also be used for Video surveillance IP cameras.



Features

- | | |
|---|--|
| <ul style="list-style-type: none"> ■ ETL verified to TIA/EIA 568-B CAT 6. ■ UL, ULc and ETL approved. ■ Very Flexible. ■ Superior performance to traditional designs. ■ 568-A and 568-B compatible. ■ This Cable exceeds TIA/EIA-568-B.2-1 e ISO/IEC 11801:2002 Class E, IEC61156-5, IEC60332-1-2, EN50288-6-1 y EN50173-1. ■ Rugged construction. ■ Backward compatible with CAT 5e and CAT 5 systems. | <ul style="list-style-type: none"> ■ Excellent price/performance ratio. ■ Available in gray and blue colors. Others upon request. ■ Four (4) 23 AWG Twisted Pairs. ■ Cover Jacket: Flame retardant Comes standard CMX, with CM, CMR and Plenum with tough thermoplastic cover Jacket with a thickness of 0,48mm. ■ Reliable 6 is a robust product. ■ Packaged in one convenient presentation: 1000 feet per box. Weight: 28lbs (12.5Kgs), easy-pull Boxes. |
|---|--|

Morphology



How to order

LP-C6TTTCCPSFCC		TTT= Type	
Category			
C6= CAT 6			
CC= Color			
WH= White	0--= Solid UTP (U/UTP).	-0= CMX	
GN= Green	1--= Stranded UTP (U/UTP).	-1= CM	
YL= Yellow	2--= FTP (F/UTP) Foil over Stranded AWG26 UTP.	-2= CMR	
BL= Blue	3--= FTP (F/UTP) Foil over Solid UTP.	-3= CMP (PLENUM)	
RD= Red	4--= SFTP (S/FTP) Braid over Individually Foiled Stranded AWG26 TP.		
BK= Black	5--= SFTP (S/FTP) Braid over individually Foiled Solid TP.		
GR= Gray	6--= Stranded U/FTP.	--0= Copper 100%	
OR= Orange	7--= Solid U/FTP.		
	8--= Stranded F/FTP.		
	9--= Solid F/FTP.		
	A--= SF/FTP Braid over Overall shield foil over individually shielded Solid Conductors TP.		
	B--= SF/FTP Braid over Overall shield foil over individually shielded Stranded Conductors TP.		
P= Packing	F= LSZH rating	CC= Color of internal Jacket	
B= 1000ft box	Blank= No if it is not LSZH Rated.	WH= White	
S= 100m spool	1= Yes if it is a LSZH rated.	GN= Green	
C= 1000ft Wood spool		YL= Yellow	
		BL= Blue	
		RD= Red	
		BK= Black	
		GR= If Gray, this code is a Blank (Standard) as in most common of outdoor types, unless the internal jacket is not gray.	
		OR= Orange	
S= Strength Member			
1= 8 Figure stranded steel strength member.			
2= 8 Figure FRP strength member.			
3= Interlock Armor.			
0= No strength member and if it is LSZH Rated in the next position.			
Blank Nothing if no strength member and it is not LSZH rated and internal jacket is Gray colored.			
Examples:			
■ LP-C6000BLB	LanPro Reliable Network Cable, CAT 6 type U/UTP (UTP), solid, 100% copper, AWG 23 Blue (CMX), with Flexible-x™ nylon core for simetry in 1000ft easy pull box.		
■ LP-C6000GRB	LanPro Reliable Network Cable, CAT 6 type U/UTP (UTP), solid, 100% copper, AWG 23 Gray (CMX), with Flexible-x™ nylon core for simetry in 1000ft easy pull box.		
■ LP-C6000BLB01	LanPro Reliable Network Cable, CAT 6 type U/UTP (UTP), solid, 100% copper, AWG 23 Blue (CMX), LSZH rated, with Flexible-x™ nylon core for simetry in 1000ft easy pull box.		
■ LP-C6000GRB01	LanPro Reliable Network Cable, CAT 6 type U/UTP (UTP), solid, 100% copper, AWG 23 Gray (CMX), LSZH rated, with Flexible-x™ nylon core for simetry in 1000ft easy pull box.		
■ LP-C6300BLB	LanPro Reliable Network Cable, CAT 6 type F/UTP (FTP), solid, 100% copper, AWG 23 Blue (CMX), with Flexible-x™ nylon core for simetry in 1000ft easy pull box.		